Frequently answered questions. ***Feel free to ask your own questions. We will answer then as soon as we can.***

Contents

- 1 Q: How do I transfer a call to a UA
- 2 Q: How can I make a delay (to make a pause between phrases?)
- 3 Q: How can I pass variables to my JavaScript?
- 4 Q: How can I print stuff inside my JavaScript?
- 5 Q: Can I save the parsed code to gain performance for often-used bits and pieces?

Q: How do I transfer a call to a UA

```
[17:02] <Verifier> MikeJ: Yeah. But I could do a session.originate and then bridge. That would wo
 i.e. connecting the caller with an UA
[17:03] <MikeJ> no.. it would block your script
[17:03] <anthm> no but if that's what you want to do then it's fine
[17:03] <anthm> calling out to somewhere is a bridge
[17:04] <anthm> transfer is to take your inbound call and go run some different script for exampl
```

Q: How can I make a delay (to make a pause between phrases?)

See: Sleep

Q: How can I pass variables to my JavaScript?

On console:

```
jsrun script.js arg1 arg2 ...
```

These can be accessed as argv[0], argv[1],.. in the script

In dialplan

```
<extension ...>
  <condition ...>
     <action application="javascript" data="script.js ${caller_id_number}"/>
   </condition>
 </extension>
```

If you're running the script as an application for originate command

```
originate sofia/internal/1000 &javascript(script.js arg1)          //single argument
originate sofia/internal/1000 '&javascript(script.js arg1 arg2)'   //multiple arguments
```

Q: How can I print stuff inside my JavaScript?

```
console_log("notice","<Whatever you need to print>");
```

--Gakul 06:00, 13 September 2008 (EDT)

Q: Can I save the parsed code to gain performance for often-used bits and pieces?